ELGOL FDM

LED WALL/CEILING LIGHT

LED Wall/Ceiling Light SPECIFICATION

Technical Parameters				Technical pictures
Product model	MF829-15W	**Product Size**	Φ270*H90mm	Picture
Features	1. Material: ABS+PS 2. 9W Epistar SMD LED. 3. Color temperature can warm white(2700K-35000K), nature white(4000K-4500K), cool white(5000K-6000K). 4. Waterproof IP65,Dust and fog protected, can be used in outdoor. 5. Black/ White Finished color for options			
Item	**Name of parameter**	**Technical parameters**		
LED Driver Parameter	Input voltage	220-240Vac		
	Freqency range	50/60Hz		
	Power Factor	PF≧0.9		
	Power Efficiency	85.0%		
	Working Temperature	-30℃～+45℃		
LED Chip Parameters	LED Type	Epistar		**Application**
	Ra	Ra＞80/90		
	Luminous Flux	1500Lm		
	CCT	700K-3500K/4000K-4500K/5000K-6000		
	Light Power	15W		
	Working Temperature	-40℃～+D2185℃		
Electrical standard	Insulation class	CLASS I		
	IP Grade	IP 65		
	Products Standard	IEC 60598-1/IEC 62031		
	Certification	CE, ROHS		
Others	Working temperature	-30℃～+45℃		
	Working humidity	10%～90%RH		
	Packing	61*30*59CM/12pcs/CTN G.W: 22KG/CTN		

© Copyright FABAE Lighting |
www.fabaelighting.com