ELGOL FD

LED BULKHEAD LIGHT



Product Information

Light Type	Bulkhead Light
Mounting	Surface
Lamp	Integral LED,COB
Beam Angle	140°
CCT	3000K/4000K/6500K
CRI	>80
Wattage	15W/20W/26W
Lumen Efficiency	85Lm/W
LED Life Time	>50,000h

Bulkhead Light aesthetically designed fixtures are suitable for new construction and retrofit applications, Better color rendering, Specular reflectors with carefully placed luminous elements offer excellent cutoff for comfortable lighting with high visual impact, Instant start and frequent switching, longer lifetime; with the push-in connectors, installation is easy and quick

General

Housing	Die Cast Aluminium
Lens/Diffuser	Opal Polycarbonate
Ambient Temperature	-0°C to 50°C
IP Rating	IP65
Body Color	Black/Grey/White


Electrical


Driver	ON-OFF
Input Voltage	AC 220~240 V
Input frequency	50 / 60 Hz
Power Factor	>0.9
THD	<15%

Applications :

Stairs, Shops, Toilets, Foyers, Bathrooms

Photometric Diagram





Wattage	Lumen	Color Temp.	Finish	Optics	Dimension (mm)DxH
15W	1275 lm	3000K	Black	110° Reflector	Ø275x80
20W	1700 lm	4000K	Grey		Ø275x80
26W	2200 lm	6500K	White		Ø275x80

FABAE LIGHTING

© Copyright FABAE Lighting |
www.fabaelighting.com